



China Deyuan Marine Fitting Co.,ltd

Add:Room1401,Unit 1,No.2 Building,Maofeng Road,Nanping,Zhuhai

Web: <http://www.deyuanmarine.com>

Attn:Miss. Michelle

Email:sales1@deyuanmarine.com

Tel:86-756-8301004

Marine pollution-prevention equipment

Item 1

Item	SPEC	PICTURE
15ppm Oily Water Separators	1. Capacity: 0.25M3/h~5.0M3/h. 2. Oil content in effluent water: less than 15ppm . 3. Certificate: CCS,EC,ABS,BV . 4. Usage: ships and vessels . 5.Standard: IMO MEPC107(49) .	

Main parameters

Type	DY-0.25	DY-0.5	DY-1.0	DY-1.50	DY-2.0	DY-2.5	DY-3.0	DY-4.0
Rated capacity (M3/H)	0.25/0.31	0.5/0.62	1.0/1.25	1.5/1.87	2/2.25	2.5/3.12	3/3.75	4.0/5.0
Power (kw)	0.75	1.10	1.10	1.10	2.20	2.20	3.0	3.0
Steam heater M2/kw	---	---	1/30	1.5/45	2/60	2.5/75	3/90	4/120
15ppm Bilge alarm	including	including	including	including	including	including	including	including
base	#5 1000*6	#6 1100*6	#6 1050*10	#8 1100*11	#8 1900*1	#8 1700*1	#10 2400*	#10 2500*

	00	90	84	30	120	500	1700	2000
dimension	1320	1460	1500	1660	1700	1900	2020	1820
Dry weight / Net weight	300/450	600/800	800/860	1060/1810	1260/2260	1500/2800	1800/3200	2100/3900
Suitable for vessels	Less than 1000 DWT	1000~5000 DWT	5~10 KDWT	10~30 KDWT	30~50 KDWT	50~100 KDWT	100~200 KDWT	100~300 KDWT

Item 2

Item	SPEC	PICTURE
15ppm Bilge water separator	1. Oily Water Separators capacity: 0.25M3/h~5.0M3/h. 2. oil content in effluent water: less than 15ppm . 3. Oily Water Separators certificate: CCS,EC,ABS,BV . 4. Oily Water Separators usage: ships and vessels. 5. Oily Water Separators standard: IMO MEPC107(49) .	

Main parameters

Type	DY-0.25	DY-0.5	DY-1.0	DY-1.50	DY-2.0	DY-2.5	DY-3.0	DY-4.0
Rated capacity (M3/H)	0.25/0.31	0.5/0.62	1.0/1.25	1.5/1.87	2/2.25	2.5/3.12	3/3.75	4.0/5.0
Power (kw)	0.75	1.10	1.10	1.10	2.20	2.20	3.0	3.0
Steam heater M2/kw	---	---	1/30	1.5/45	2/60	2.5/75	3/90	4/120
15ppm Bilge alarm	including	including	including	including	including	including	including	including
base	#5	#6	#6	#8	#8	#8	#10	#10

	1000*600	1100*690	1050*1084	1100*1130	1900*1120	1700*1500	2400*1700	2500*2000
dimension	1320	1460	1500	1660	1700	1900	2020	1820
Dry weight / Net weight	300/450	600/800	800/860	1060/1810	1260/2260	1500/2800	1800/3200	2100/3900
Suitable for vessels	《1000 DWT	1000~5000 DWT	5~10 KDWT	10~30 KDWT	30~50 KDWT	50~100 KDWT	100~200 KDWT	100~300 KDWT

Item 3

Item	SPEC	PICTURE
Marine Bilge water separator	1. Oily Water Separators capacity: 0.25M3/h~5.0M3/h . 2. oil content in effluent water: less than 15ppm . 3. Oily Water Separators certificate: CCS,EC,ABS,BV . 4. Oily Water Separators usage: ships and vessels . 5. Oily Water Separators standard: IMO MEPC107(49) .	

Main parameters

Type	DY-0.25	DY-0.5	DY-1.0	DY-1.50	DY-2.0	DY-2.5	DY-3.0	DY-4.0
Rated capacity (M3/H)	0.25/0.31	0.5/0.62	1.0/1.25	1.5/1.87	2/2.25	2.5/3.12	3/3.75	4.0/5.0
Power (kw)	0.75	1.10	1.10	1.10	2.20	2.20	3.0	3.0
Steam heater M2/kw	---	---	1/30	1.5/45	2/60	2.5/75	3/90	4/120
15ppm Bilge alarm	including	including	including	including	including	including	including	including
base	#5 1000*	#6 1100*6	#6 1050*10	#8 1100*11	#8 1900*1	#8 1700*1	#10 2400*	#10 2500*

	600	90	84	30	120	500	1700	2000
dimension	1320	1460	1500	1660	1700	1900	2020	1820
Dry weight/ Net weight	300/450	600/800	800/860	1060/1810	1260/2260	1500/2800	1800/3200	2100/3900
Suitable for vessels	《 1000 DWT	1000~5000 DWT	5~10 KDWT	10~30 KDWT	30~50 KDWT	50~100 KDWT	100~200 KDWT	100~300 KDWT

Item 4

Item	SPEC	PICTURE
Marine Sewage Treatment Plant	1.Capacity:10~250person . 2.Standard: IMO MEPC159(55),MARPOL 73/78 . 3.Certificate : CCS,EC,BV,ABS . 4.Usage: ships &vessels .	

Main parameters

Model		15	20	25	30	40	50	60	80	100	150	200	250
Load	Average load	1190	1540	1890	2310	3080	3780	4480	6020	7700	11200	14700	18200
	L/d												
	Peak load	149	193	237	289	385	473	560	753	963	1400	1838	2275
	L/h												
	Organic load	0.595	0.77	0.945	1.155	1.54	1.89	2.24	3.01	3.85	5.6	7.35	9.1
	kgBOD5/d												
Rated capacity(P)		15	20	25	30	40	50	60	80	100	150	200	250
Max capacity(P)		17	22	27	33	44	54	64	86	110	160	210	260
Electricity		AC380V, 50HZ, 3φ/AC						440, 60Hz, 3φ					
Power(KW)		1.5	1.5	1.5	1.5	1.5	2	2	2.5	2.5	3		
External dimensions		1550×	1650×	1850×	1950×	1800×	1900×	2100×	2500×	2500×	3150×		
L*W*H(mm)		1400×	1400×	1500×	1500×	1700×	1700×	1700×	1900×	1900×	2400×		
		1600	1600	1635	1635	1900	1950	2000	2150	2300	2300		

Weight	Dry weight	1150	1200	1250	1350	1500	1750	1950	2150	2900	3800	
	(Kg)											
	Wet weight	2600	2933	3210	3928	4689	5665	6486	8100	10400	14680	
	(Kg)											
Discharge standard		TSS35mg/L, BOD525mg/L, COD125mg/L, Coli form100pcs/100ml, PH:68.5										

Item 5

Item	SPEC	PICTURE
Biochemical Marine Sewage treatment plant	1.capacity:10~250person . 2.standard: IMO MEPC159(55),MARPOL 73/78 . 3.certificate : CCS,EC,BV,ABS . 4.usage: ships &vessels .	

Main parameters

Model		15	20	25	30	40	50	60	80	100	150	200	250
Load	Average load	1190	1540	1890	2310	3080	3780	4480	6020	7700	11200	14700	18200
	L/d												
	Peak load	149	193	237	289	385	473	560	753	963	1400	1838	2275
	L/h												
	Organic load	0.595	0.77	0.945	1.155	1.54	1.89	2.24	3.01	3.85	5.6	7.35	9.1
	kgBOD5/d												
Rated capacity(P)		15	20	25	30	40	50	60	80	100	150	200	250
Max capacity(P)		17	22	27	33	44	54	64	86	110	160	210	260
Electricity		AC380V, 50HZ, 3φ/AC 440, 60Hz, 3φ											
Power(KW)		1.5	1.5	1.5	1.5	1.5	2	2		2.5	2.5	3	
External dimensions		1550×	1650×	1850×	1950×	1800×	1900×	2100×		2500×	2500×	3150×	

L*W*H(mm)		1400×	1400×	1500 ×	1500 ×	1700×	1700	1700×	1900×	1900×	2400×
		1600	1600	1635	1635	1900	1950	2000	2150	2300	2300
Weight	Dry weight	1150	1200	1250	1350	1500	1750	1950	2150	2900	3800
	(Kg)										
	Wet weight	2600	2933	3210	3928	4689	5665	6486	8100	10400	14680
Discharge standard		TSS35mg/L, BOD525mg/L, COD125mg/L, Coli form100pcs/100ml, PH:68.5									

Item 6

Item	SPEC	PICTURE
Marine sewage treatment Unit	Marine Sewage Treatment Plant: 1.capacity:10~250person. 2.standard: IMO MEPC159(55),MARPOL 73/78 . 3.certificate : CCS,EC,BV,ABS . 4.usage: ships & vessels .	

Main parameters

Model	15	20	25	30	40	50	60	80	100	150	200	250
L/d												
Peak load	149	193	237	289	385	473	560	753	963	1400	1838	2275
Organic load	0.595	0.77	0.945	1.155	1.54	1.89	2.24	3.01	3.85	5.6	7.35	9.1
Rated capacity(P)	15	20	25	30	40	50	60	80	100	150	200	250
Max capacity(P)	17	22	27	33	44	54	64	86	110	160	210	260
Electricity	AC380V, 50HZ, 3φ/AC					440, 60Hz, 3φ						
Power(KW)	1.5	1.5	1.5	1.5	1.5	2	2	2.5	2.5	3		

External dimensions	1550×	1650×	1850×	1950×	1800×	1900×	2100×	2500×	2500×	3150×	
L*W*H(mm)	1400×	1400×	1500×	1500×	1700×	1700	1700×	1900×	1900×	2400×	
	1600	1600	1635	1635	1900	1950	2000	2150	2300	2300	
Weight											
	1150	1200	1250	1350	1500	1750	1950	2150	2900	3800	
	2600	2933	3210	3928	4689	5665	6486	8100	10400	14680	
Discharge standard	TSS35mg/L, BOD525mg/L, COD125mg/L, Coli form100pcs/100ml, PH:68.5										

Item 7

Item	SPEC	PICTURE
15ppm Bilge Water Alarm	1) Measuring range: 0-30ppm (display range 0-80ppm) 2) Measurement precision: (15ppm alarm) $\pm$ 5ppm (meet the IMO standard) 3) Display type : LED digital tube 4) 15ppm bilge water Alarm Alarm indication: 4 red LED 5) 2-way alarm relay 6) Rated capacity of relay contact 250VAC 3A (non-emotional) 7) 15ppm bilge water Alarm Response time $\leq$ 5 seconds 8) Output signal 4-20mA 9) Environment temperature 0 - 55 Celsius degree 10) bilge water Alarm Relative humidity $\leq$ 93% 11) Sample liquid temperature 1 - 55Celsius degree 12) Sample liquid pressure 0.1-0.6MPa 13) Sample liquid flow of 0.1-4L / min 14) Protection class IP55 15) Main power supply 220/110VAC 50Hz/60Hz 16) Power Consumption $\leq$ 20VA 17) Overall dimension 400mm $\times$ 300mm $\times$ 160mm 18) Meet the standard IMO. Res. MEPC. 107 (49) resolution	

Item 8

Item	SPEC	PICTURE
15ppm bilge alarm for bilge water separator or	1) Measuring range: 0-30ppm (display range 0-80ppm) 2) Measurement precision: (15ppm alarm) $\pm$ 5ppm (meet the IMO standard) 3) Display type : LED digital tube 4) 15ppm bilge water Alarm Alarm indication: 4 red LED 5) 2-way alarm relay 6) Rated capacity of relay contact 250VAC 3A (non-emotional) 7) 15ppm bilge water Alarm Response time $\leq$ 5 seconds 8) Output signal 4-20mA 9) Environment temperature 0 $^{\circ}$ C - 55 $^{\circ}$ C 10) bilge water Alarm Relative humidity $\leq$ 93% 11) Sample liquid temperature 1 - 55 $^{\circ}$ C 12) Sample liquid pressure 0.1-0.6MPa 13) Sample liquid flow of 0.1-4L / min 14) Protection class IP55 15) Main power supply 220/110VAC 50Hz/60Hz 16) Power Consumption $\leq$ 20VA 17) Overall dimension 400mm $\times$ 300mm $\times$ 160mm 18) Meet the standard IMO. Res. MEPC. 107 (49) resolution	

Item 9

Item	SPEC	PICTURE
15ppm bilge alarm	1) Measuring range: 0-30ppm (display range 0-80ppm) 2) Measurement precision: (15ppm alarm) $\pm$ 5ppm (meet the IMO standard) 3) Display type : LED digital tube 4) 15ppm bilge water Alarm Alarm indication: 4 red LED 5) 2-way alarm relay 6) Rated capacity of relay contact 250VAC 3A (non-emotional) 7) 15ppm bilge water Alarm Response time $\leq$ 5 seconds 8) Output signal 4-20mA	

	9) Environment temperature 0 °C - 55 °C 10) bilge water Alarm Relative humidity ≤ 93% 11) Sample liquid temperature 1 - 55 °C 12) Sample liquid pressure 0.1-0.6MPa 13) Sample liquid flow of 0.1-4L / min 14) Protection class IP55 15) Main power supply 220/110VAC 50Hz/60Hz 16) Power Consumption ≤ 20VA 17) Overall dimension 400mm × 300mm × 160mm 18) Meet the standard IMO. Res. MEPC. 107 (49) resolution	
--	--	--

Item 10

Item	SPEC	PICTURE
15ppm bilge alarm for oily water separator	1) Measuring range: 0-30ppm (display range 0-80ppm) 2) Measurement precision: (15ppm alarm) ± 5ppm (meet the IMO standard) 3) Display type : LED digital tube 4) 15ppm bilge water Alarm Alarm indication: 4 red LED 5) 2-way alarm relay 6) Rated capacity of relay contact 250VAC 3A (non-emotional) 7) 15ppm bilge water Alarm Response time ≤ 5 seconds 8) Output signal 4-20mA 9) Environment temperature 0 °C - 55 °C 10) bilge water Alarm Relative humidity ≤ 93% 11) Sample liquid temperature 1 - 55 °C 12) Sample liquid pressure 0.1-0.6MPa 13) Sample liquid flow of 0.1-4L / min 14) Protection class IP55 15) Main power supply 220/110VAC 50Hz/60Hz 16) Power Consumption ≤ 20VA 17) Overall dimension 400mm × 300mm × 160mm 18) Meet the standard IMO. Res. MEPC. 107 (49) resolution	

Item 11

Explosion Proof Oil Content Meter	Precision: 0---20PPM$\pm$2PPM, 20—199PPM$\pm$10% . 2.Alarm indication: Red LED . 3. Pressure of sample water: 0.01~0.6Mpa . 4. Runoff of sample water : 0.15---4L/min . 5.Operation voltage: 220VAC, 50/60Hz . 6.Power: 25W .	
--	---	---

Item 12

Oil Content Meter	1.oil content meter Precision: 0---20PPM$\pm$2PPM, 20—199PPM$\pm$10% . 2.oil content meter Alarm indication: Red LED . 3.oil content meter Pressure of sample water: 0.01~0.6Mpa . 4.oil content meter Runoff of sample water : 0.15---4L/min . 5.Operation voltage: 220VAC, 50/60Hz . 6.Power: 25W .	
-------------------	---	--

Item 13

Marine Oil Content Meter	1.oil content meter Precision: 0---20PPM$\pm$2PPM, 20—199PPM$\pm$10% . 2.oil content meter Alarm indication: Red LED . 3.oil content meter Pressure of sample water: 0.01~0.6Mpa . 4.oil content meter Runoff of sample water : 0.15---4L/min . 5.Operation voltage: 220VAC, 50/60Hz . 6.Power: 25W .	
-----------------------------	--	---

Item 14

Marine Fresh Water Generator	Model: Fresh Water Generator . Capacity: 5~50T/D . 3. Compact design for easy installation . 4. high quality titanic plate, 316LSS & Al-Bronze for other component.	
------------------------------	---	---

Main parameters

Mode(T/D)	FWG-5	FWG-10	FWG-16	FWG-20	FWG-30	FWG-50
capacity	5	10	16	20	30	50
Length(mm)	770	970	970	1160	1400	1400
Width(mm)	600	870	1150	1150	1250	1450
Height(m m)	960	1150	1150	1415	1550	1550
Dry weight(kg)	300	650	900	1150	1350	1450
Operation weight(kg)	350	700	950	1250	1450	1600

Item 15

Marine Fresh Water Maker	1. Model: Fresh Water Generator . 2. Capacity: 5~50T/D . 3. Compact design for easy installation . 4. high quality titanic plate, 316LSS & Al-Bronze for other component.	
--------------------------	---	--

Main parameters

Mode(T/D)	FWG-5	FWG-10	FWG-16	FWG-20	FWG-30	FWG-50
-----------	-------	--------	--------	--------	--------	--------

capacity	5	10	16	20	30	50
Length(mm)	770	970	970	1160	1400	1400
Width(mm)	600	870	1150	1150	1250	1450
Height(m m)	960	1150	1150	1415	1550	1550
Dry weight(kg)	300	650	900	1150	1350	1450
Operation weight(kg)	350	700	950	1250	1450	1600

Item 16

Seawater Desalting Plant	1.Model:Fresh Water Generator . 2.Capacity:5~50T/D . 3.Compact design for easy installation . 4.high quality titanic plate,316LSS&Al-Bronze for other component.	
--------------------------	--	---

Main parameters

Mode(T/D)	FWG-5	FWG-10	FWG-16	FWG-20	FWG-30	FWG-50
capacity	5	10	16	20	30	50
Length(mm)	770	970	970	1160	1400	1400
Width(mm)	600	870	1150	1150	1250	1450
Height(m m)	960	1150	1150	1415	1550	1550
Dry weight(kg)	300	650	900	1150	1350	1450
Operation weight(kg)	350	700	950	1250	1450	1600

Item 17

Seawater Desalting Unit	1.Model:Fresh Water Generator . 2.Capacity:5~50T/D . 3.Compact design for easy installation . 4.high quality titanic plate,316LSS&Al-Bronze for other component.	
-------------------------	--	--

Main parameters

Mode(T/D)	FWG-5	FWG-10	FWG-16	FWG-20	FWG-30	FWG-50
capacity	5	10	16	20	30	50
Length(mm)	770	970	970	1160	1400	1400
Width(mm)	600	870	1150	1150	1250	1450
Height(m m)	960	1150	1150	1415	1550	1550
Dry weight(kg)	300	650	900	1150	1350	1450
Operation weight(kg)	350	700	950	1250	1450	1600

Item 18

Marine Reverse Osmosis Fresh Water Generator	1.Type:Reverse Osmosis fresh water geneator . 2.Capacit:5~1000T/D . 3.flow mimic diagram indicates working condition . 4.High standard R.O. elements reducing maintenance cost .	
---	---	---

Item 19

Marine Reverse Osmosis desalting plant	1.Type:Reverse Osmosis fresh water geneator . 2.Capacit:5~1000T/D . 3.flow mimic diagram indicates working condition . 4.High standard R.O. elements reducing maintenance cost .	
---	---	--

Item 20

Marine Reverse Osmosis desalting unit	1.Type:Reverse Osmosis fresh water geneator . 2.Capacit:5~1000T/D . 3.flow mimic diagram indicates working condition . 4.High standard R.O. elements reducing maintenance cost .	
---------------------------------------	--	--

Item 21

UV-sterilizer	1.Type:Marine UV sterilizer . 2.Capacity:1.3m3/h~50m3/h . 3.Stainless steel chamber with no corrosion . 4.Long life UV lamp up to 8000 HRS .	
---------------	--	---

Item 22

UV-sterilizer for marine sewage treatment plant	1.Type:Marine UV sterilizer . 2.Capacity:1.3m3/h~50m3/h . 3.Stainless steel chamber with no corrosion . 4.Long life UV lamp up to 8000 HRS .	
---	--	--

Main parameters

Model	UIV-1.3	UIV-4	UIV-10	UIV-20	UIV-30	UIV-50
Capacity (m ³ /h)	1.3	4	10	20	30	50

Item 23

Marine UV-sterilizer	1.Type:Marine UV sterilizer . 2.Capacity:1.3m3/h~50m3/h . 3.Stainless steel chamber with no corrosion . 4.Long life UV lamp up to 8000 HRS .	 The image shows a vertical stainless steel UV sterilizer unit with a yellow label at the top. To its right is a grey control panel with a green emergency stop button, a red power button, and several indicator lights and switches. A watermark 'www.deyuanmarine.co' is visible across the image.
--	---	--

Item 24

Silver Ion Sterilizer	Type: silver ion sterilizer . 2.Capacity: Max. 15m3/h; 3.0.04ppm dosage . 4.New designed with good quality and competitive price.	 The image shows a silver ion sterilizer unit with a digital display and control buttons on a grey panel. It is connected to a stainless steel chamber with various pipes and fittings. A watermark 'www.deyuanmarine.co' is visible across the image.
---	--	--

Item 25

Marine Silver Ion Sterilizer	Type: silver ion sterilizer . 2.Capacity: Max. 15m3/h; 3.0.04ppm dosage . 4.New designed with good quality and competitive price.	 The image shows a marine silver ion sterilizer unit with a digital display and control buttons on a grey panel. It is connected to a stainless steel chamber with various pipes and fittings. A watermark 'www.deyuanmarine.co' is visible across the image.
--	--	--

Item 26

Rehardening water filter	1.Type:rehardening water filter/mineralizer . 2.Capacity:1.5M3/H~25M3/H . 3.Good quality with compectitive price .	
-----------------------------	---	---

Main parameters

Model	FIL-1.5	FIL-3	FIL-5	FIL-8	FIL-10	FIL-15	FIL-25
Capacity (m ³ /h)	1.5	3	5	8	10	15	25

Item 27

Mineralizer	1.Type:rehardening water filter/mineralizer . 2.Capacity:1.5M3/H~25M3/H . 3.Good quality with compectitive price	
-------------	---	--

Main parameters

Model	FIL-1.5	FIL-3	FIL-5	FIL-8	FIL-10	FIL-15	FIL-25
Capacity (m ³ /h)	1.5	3	5	8	10	15	25

Item 28

Marine Incinerator	1.Heat capacity:1285700Kcal/h(1495kw) 2.Incinerator capacity: a.solid waste feeding:600L/charge b. Waste oil:171L/h w/bilge water:162L/h without b.w C.bilge water:237L/h Liquid waste containing max.water less than50% 3.Diesel consumption:18-36L/h 4.Power consumption:31KW 5.Dimensions&weight: GS1000C 2926*1807*2140mm 4450KG	 www.deyuanmarine.com
----------------------------------	--	---

Main parameters

	INC-18	INC-50	INC-50A	INC-80
Models	Marine Incinerator	Marine Incinerator	Marine Incinerator	Marine Incinerator
	180,000 Kcal/H	500,000 Kcal/H	500,000 Kcal/H	800,000 Kcal/H

Item 29

Marine Incinerators	1.Heat capacity:1285700Kcal/h(1495kw) 2.Incinerator capacity: a.solid waste feeding:600L/charge b. Waste oil:171L/h w/bilge water:162L/h without b.w C.bilge water:237L/h Liquid waste containing max.water less than50% 3.Diesel consumption:18-36L/h 4.Power consumption:31KW 5.Dimensions&weight: GS1000C 2926*1807*2140mm 4450KG (Flue gas fan)with frequency inverter:DN500&695	
---------------------	---	---

Main parameters

	INC-18	INC-50	INC-50A	INC-80
Models	Marine Incinerator	Marine Incinerator	Marine Incinerator	Marine Incinerator
	180,000 Kcal/H	500,000 Kcal/H	500,000 Kcal/H	800,000 Kcal/H

Item 30

Marine Incinerator for ships	1.Heat capacity:1285700Kcal/h(1495kw) 2.Incinerator capacity: a.solid waste feeding:600L/charge b. Waste oil:171L/h w/bilge water:162L/h without b.w C.bilge water:237L/h Liquid waste containing max.water less than50% 3.Diesel consumption:18-36L/h 4.Power consumption:31KW 5.Dimensions&weight: GS1000C 2926*1807*2140mm 4450KG (Flue gas fan)with frequency inverter:DN500&695	
------------------------------	---	--

Main parameters

Models	INC-18	INC-50	INC-50A	INC-80
	Marine Incinerator	Marine Incinerator	Marine Incinerator	Marine Incinerator
	180,000 Kcal/H	500,000 Kcal/H	500,000 Kcal/H	800,000 Kcal/H

Item 31

Oil Discharge Monitoring and Control System	The MARPOL 73/78 Convention specifies that oil tankers with a gross tonnage of 150 tons and above shall be equipped with an Oil Discharge Monitoring and Control System (ODMS). This system must be arranged to monitor all discharges overboard of oil contaminated water from the ballast water. The CleanTrack 1000 Oil Discharge Monitoring and Control System is approved and certified in accordance with IMO Res. MEPC 108(49). The approval covers the ability of the system to monitor different kinds of crude oils, "black / white substances", as well as a number of identified chemicals allowed to be carried in oil tanker under the criteria for "oil-like substances". The CleanTrack 1000 system is approved by the Marine Administration as specified in the IMO regulations. In addition to this, the system is type approved by the major classification societies. It has also the "MED"-Marine Directive approval, for equipment to be installed onboard ships, in accordance with the European council Directive 96/98/EC.	 The image shows a rectangular electronic control unit for the CleanTrack 1000 system. It features a small monochrome LCD screen displaying a grid pattern. To the right of the screen are several indicator lights and a large rotary selector switch. The unit is labeled 'OIL DISCHARGE MONITOR CleanTrack 1000' and 'BRANDSTROM SYSTEMS'. A watermark 'www.deyuanmarine.com' is visible across the unit.
---	--	---