



China Deyuan Marine Fitting Co.,Ltd

Add:Room1401,Unit 1,No.2 Building,Maofeng Road,Nanping,Zhuhai

Website:<http://www.deyuannmarine.com>


Attn:Miss.Michelle

E-mail:sales1@deyuannmarine.com


[Tel:86-756-8301004](tel:86-756-8301004) or cell phone15913202953

Air breathing apparatus

Item 1


Item	SPEC	PICTURE
SCBA breathing apparatus	air Model:RHZK5/30,RHZK6/30 Working pressure:30Mpa/300bar Volume:5L,6L Air deposite:1500L,1800L Using time:40-50min,50-60min Alarm Pressure:4-6Mpa Weight:≤16,≤18 Packing:710*290*430	

Item 2


Item	SPEC	PICTURE
RHZK5/30 respirators	Air Model:RHZK5/30,RHZK6/30 Working pressure:30Mpa/300bar Volume:5L,6L Air deposite:1500L,1800L Using time:40-50min,50-60min Alarm Pressure:4-6Mpa Weight:≤16,≤18 Packing:710*290*430	




Item 3

Item	SPEC	PICTURE
RHZK6/30 respirator	Air Model:RHZK5/30,RHZK6/30 Working pressure:30Mpa/300bar Volume:5L,6L Air deposite:1500L,1800L Using time:40-50min,50-60min Alarm Pressure:4-6Mpa Weight:≤16,≤18 Packing:710*290*430	

Item 4


Item	SPEC	PICTURE
RHZK6.8L/30 Respirator	Air Model:RHZK5/30,RHZK6/30 Working pressure:30Mpa/300bar Volume:6.8L Air deposite:1500L,1800L Using time:40-50min,50-60min Alarm Pressure:4-6Mpa Weight:≤16,≤18 Packing:710*290*430	

Item 5


Item	SPEC	PICTURE
RHZK9/30 Respirator	Air Model:RHZK5/30,RHZK6/30 Working pressure:30Mpa/300bar Volume:5L,6L Air deposite:2040L,2700L,2040*2L Using time:40-50min,50-60min Alarm Pressure:4-6Mpa Weight:≤16,≤18 Packing:710*290*430	




Item 6

Item	SPEC	PICTURE
SCBA compressed breathing apparatus	Model:RHZK5/30,RHZK6/30 Working pressure:30Mpa/300bar Volume:5L,6L Air deposite:1500L,1800L Using time:40-50min,50-60min Alarm Pressure:4-6Mpa Weight:≤16,≤18 Packing:710*290*430	

Item 7

Item	SPEC	PICTURE
self-contained positive pressure air breathing apparatus	Model:RHZK5/30,RHZK6/30 Working pressure:30Mpa/300bar Volume:5L,6L Air deposite:1500L,1800L,2040L,2700L,2040*2L Using time:40-50min,50-60min Alarm Pressure:4-6Mpa Weight:≤16,≤18 Packing:710*290*430	


Item 8

Item	SPEC	PICTURE
Emergency Escape breathing Device	Model:THDF10/I,THDF15/I Volume:2.2L,3L Rating working pressure:21Mpa Duration time:≥10mins,≥15mins Weight:≤6kg,8.5kg	




Air breathing apparatus inflator pump

Item 9

Item	SPEC	PICTURE
Air breathing apparatus inflator pump	Type:JUNIOR II-B Capacity:100L/MIN Features:compact design,light weight,durable,lower noise,easy operation Max working pressure:330bar Size:660*360mm*420mm	

Item 10

Item	SPEC	PICTURE
Air respirator inflator pump	1.Standard:EN12021 . 2.Capacity:100L/MIN . 3.Working pressure:225bar~300bar m. 4.Motor:12L:25min,225bar 12L:35min,300bar 5.Size:650mm*350mm*390 mm . 6.Weight:39kg . 7.Noise:83dB-ISO3746 .	

Personal Fire Fighting Equipment

Item 11

Item	SPEC	PICTURE
Personal Fire Fighting Equipment	<p>1.Product standard: According to International Code for Fire Safety Systems .</p> <p>2.Approval: CCS(China Classification Society of shipping) .</p> <p>3.Application:Offshore,commercial ships .</p> <p>Include:</p> <p>Aluminium coated protective clothing 1pcs</p> <p>SCBA breathing apparatus(5L) 1 SET</p> <p>Fire safety lifeline 1pcs</p> <p>Explosion-proof lamp 1pcs</p> <p>Fire waist axe 1pcs</p> <p>Fiberglass helmet 1pcs</p> <p>Rubber boots 1pcs</p> <p>Waist belt 1pcs</p> <p>Glass fiber reinforced plastic case 1pcs</p>	



Item 12

Item	SPEC	PICTURE
Fireman Protective suit /Heat insulation suit	<p>1.Heat radiation resistance:Under heat radiation of 10KW/M2,about 30 seconds,the inside surface temperature shall rise no more than 25℃ .</p> <p>2.Waterproof: static hydraulic pressure ≥4000Pa .</p> <p>3.Size:M,L,XL .</p> <p>4.IMPA Code:33 09 03 .</p> <p>5.Approval:CCS/EC .</p>	

Item 13

<p>Heavy-duty Chemical protective suit</p>	<ol style="list-style-type: none"> 1.Color:Red/yellow 2.Packing Size:580*420*360mm (2set per carton) 3.Size:one size up to 190CM 4.Weight:6kg 5.Sewing to the use of frame-resistant and adhesive strong the Nylon,with both-sides being covering with Chemical protective and fire resistant rubber.The seal structure,made full seal structure by normal big windows connected the hood,chemical protective suit/boots/gloves 6.Certificate:CCS/EC 	
--	--	--


Item 14

<p>Light-Duty Chemical suit</p>	<ol style="list-style-type: none"> 1.Size: one size up to 190cm 2.Weight:5kg 3.Using the coverall structure to ensure safety covered the users,consist of the chemical protective hoods/clothing/gloves 4.Packing size:580*420*360mm (2pcs/carton 10kg) 5.Application:For fireman or workers working in accident side which has acid and alkali 6.Chemicals,SCBA should be equipped outside the suit 7.Material:Polyamide fabric double coated with PVC 	 
-------------------------------------	--	--


Item 15

<p>Fire fighting suit</p>	<p>1.Standard: According to the standard Q/02 TXF 001-2000</p> <p>Component part:</p> <p>2.Nomes outer shell(nomex 93%,KEVLAR 5%,P140 2%),</p> <p>3.waterproof and ventilation layer,</p> <p>4.heat-resisting layer,and comfortable inner.</p> <p>5.Application:Basic protective garment for fire fighting</p> <p>6.Composition: Coat and pants.</p> <p>7.Size:S(160-165),M(165-170),L(170-175),XL(175-180),XXL(180-185)</p>	
---------------------------	--	--

Item 16

<p>Handheld Explosion-proof light</p>	<p>1.Bulb:7.2V/05A .</p> <p>2.Duration: ≥3h .</p> <p>3.Explosion-proof class:IP65 .</p> <p>4.Temperature resistance:-20℃~+50℃ .</p> <p>5.Battery:Dry battery .</p> <p>6.IMPA Code:33 06 07 .</p> <p>7.Approval:CCS .</p>	
---------------------------------------	--	--

Item 17

<p>Straight Portable explosion light</p>	<p>1.Bulb:2.4V/0.5A .</p> <p>2.Duration: ≥5h .</p> <p>3.Explosion-proof class:Exe ib IIC T6 .</p> <p>4.Temperature resistance:-20℃~+40℃ .</p> <p>5.IMPA Code:33 06 07 .</p> <p>6.Approval:CE .</p>	
--	--	--

